FIRST CHOICE DENTAL LAB

5413 Walnut Ave., #2A,
Downers Grove, IL 60515

www.firstchoicelab.com
630-541-7666

Abutment Torque Settings and Screwdriver Type

	Manufacturer	Torque N-cm	Driver for Titanium Screw
Dentsply Sirona	ANKLYOS®C?X-C/ 3.5, 4.5, 5.5, 7.0 (non-ind)	15	1.0 mm hex
	ANKLYOS®C?X-C/ 3.5, 4.5, 5.5, 7.0 (indexed)	15	1.0 mm hex
	OsseoSpeed™ EV 3.0 - Green	15	0.050" - 1.25 mm hex
	OsseoSpeed™ EV 3.6 - Purple	25	0.050" - 1.25 mm hex
	OsseoSpeed™ EV 4.2 - Yellow	25	0.050" - 1.25 mm hex
	OsseoSpeed™ EV 4.8 - Blue	25	0.050" - 1.25 mm hex
	OsseoSpeed™ EV 5.4 - Brown	25	0.050" - 1.25 mm hex
	OsseoSpeed™ Profile EV 4.2 - Yellow	25	0.050" - 1.25 mm hex
	OsseoSpeed™ Profile EV 4.8 - Blue	25	0.050" - 1.25 mm hex
	OsseoSpeed™/OsseoSpeed™ TX 3.0 - Yellow	15	0.050" - 1.25 mm hex
	OsseoSpeed™/OsseoSpeed™ TX 3.5, 4.0 - Aqua	20	0.050" - 1.25 mm hex
	OsseoSpeed™/OsseoSpeed™ TX 4.5, 5.0 - Lilac	25	0.050" - 1.25 mm hex
Nobel Biocare™	NobelActive™ 3.0	15	Unigrip
	NobelActive™ NP 3.5	35	Unigrip
	NobelActive™ RP 4.3, WP 5.0	35	Unigrip
	Nobel Replace™ NP 3.5	35	Unigrip
	Nobel Replace™ NP 4.3	35	Unigrip
	Nobel Replace™ WP 5.0	35	Unigrip
	Nobel Replace™ 6.0	35	Unigrip
	Branemark System™ NP 3.3	20	0.048" hex
	Branemark System™ RP 3.75, 4.0	20	0.048" hex
	Branemark System™ WP 5.0, 5.5	20	0.048" hex
straumann	Bone Level 3.4 NC (Narrow CrossFit™)	35	SCS
	Bone Level 4.1, 4.8 RC (Regular CrossFit™)	35	SCS
	Standard/Standard Plus 4.8 RN (Regular Neck)	35	SCS
	Standard/Standard Plus 4.8 WN (Wide Neck)	35	SCS
	Standard Plus 3.3 NN (Narrow Neck)	35	SCS
NEODENT A STRAUMANN GROUP BRAND	GM	20	Neodent
	CM	15	0.9 mm hex
BIOMET 3i™	Certain™ 3.25, 4.0, 4/3, 5.0, 5/4, 6.0	20	0.048" hex
	Certain™ Prevail™ 3/4/4 (3.4), 4/5/4, 5/6/5, 4/3, 5/4, 6/5	20	0.048" hex
	Certain™ XP 4/5, 5/6	20	0.048" hex
	Miniplant™ 3.25	20	0.048" hex
	Osseotite™ 3.75, 4.0, 5.0, 6.0	20	0.048" hex
	Osseotite™ XP 4/5, 5/6	35	0.048" hex
BIOHORIZONS®	Internal 3.5, 4.5, 5.7	30	0.050" - 1.25 mm hex
	Tapered Internal 3.5, 4.5, 5.7	30	0.050" - 1.25 mm hex
	External Implant 3.5	30	0.050" - 1.25 mm hex
	External Implant 4.0, 5.0	30	0.050" - 1.25 mm hex
	Tapered Pro Conical Narrow, Regular	20	0.050" - 1.25 mm hex
camlog	Screw-Line Implant 3.3	20	0.050" - 1.25 mm hex
	Screw-Line/Root-Line Implant 3.8, 4.3, 5.0, 6.0	20	0.050" - 1.25 mm hex
HIOSSEN	Hiossen/Osstem HG mini (3.5)	30	1.2 mm hex
	Hiossen/Osstem standard 4.0, 4.5, 5.0	30	1.2 mm hex
IMTEC DENTAL IMPLANTS	Imtec® 3M Endure™	35	0.050" - 1.25 mm hex
IMPLANT DIRECT™	Implant Direct Legacy™	30	0.050" - 1.25 mm hex
MIS MAKE IT SIMPLE	MIS® Biocom & Seven	30	0.050" - 1.25 mm hex
OCO BIOMEDICAL	OCO Biomedical	20	0.050" - 1.25 mm hex
THOMMEN Medical	Thommen SPI® 3.5	15	Four Lobe
	Thommen SPI® 4.0, 4.5, 5.0, 6.0	20	Four Lobe
zimmer	Screw Vent™ 3.3, 3.7, 4.5	30	0.050" - 1.25 mm hex
	Screw Vent™ 3.3, 3.7, 4.5 friction fit	30	0.050" - 1.25 mm hex
	Tapered Screw Vent™ 3.5, 4.5, 5.7	30	0.050" - 1.25 mm hex
	Tapered Screw Vent™ 3.5, 4.5, 5.7 friction fit	30	0.050" - 1.25 mm hex
	SwissPlus™ 4.8	30	0.050" - 1.25 mm hex

CAD/CAM custom titanium and zirconia abutments utilize the same torque and driver settings as the original implant manufacturer